
DIAPHRAGM DELUGE VALVE LOCAL RESET

MODEL AG 400-L EXTERNAL AND LOCAL RESET
Electric Actuation
(Ductile Iron, Cast Steel & Nickel Aluminum Bronze)

c UL us LISTED 15133

Valve Closed





PRODUCT DESCRIPTION

Deluge Valve is known as a system control valve in a deluge system, used for fast application of water in a spray system. Deluge valve protects areas such as power transformer installation, storage tank, conveyor protection and other industrial application etc. With the addition of foaming agent deluge valve can be used to protect aircraft hangar and inflammable liquid fire.

TECHNICAL DATA

Model	AG 400-L
Materials	D: Ductile Iron ASTM A536 S: Cast Steel ASTM A216 WCB N: Nickel Aluminum Bronze BS1400 Gr AB2
Nominal size	DN50 (2”), DN80 (3”), DN100 (4”), DN150 (6”) & DN200 (8”)
Service pressure	1.4 to 17.5 Bar (20 to 250 psi)
Threaded opening	BSPT
Installation position	Vertical or Horizontal mounting
Factory hydrostatic test pressure	35 Kg/sq.cm. (500 psi)
Flange connection	ANSI B 16.5 Class 150
Service	Without removal from line
Trim	Galvanized tubing and fittings and brass accessories Stainless Steel (SS-316) tubing and fittings and brass accessories Stainless Steel (SS-316) tubing, fittings and accessories Monel and Nickel Aluminum Bronze tubing, fittings and accessories
Net weight without trim	DN 50 - 32 Kg DN 80 - 35 Kg DN 100 - 50 Kg DN 150 - 79 Kg DN 200 - 153 Kg
Finish	Internal and external surfaces epoxy coated for extra protection Red RAL 3000


C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

OPERATION: MODEL AG 400-L ELECTRIC ACTUATION


The Model AG 400-L from AG Fire Sprinkler is suitable for systems that include electric fire detection and a piping system with a wide variety of open nozzles.

In the SET position, the line-pressure supplied to the main valve's control chamber **(1)** via the priming line **(2)** and through a Manual Reset **(3)**, is trapped by the Manual Reset **(3)** internal check valve, by a closed 2-Way Solenoid Valve **(4)**, and by a closed Manual Emergency Release **(5)**. The trapped pressure holds the main valve's diaphragm and plug against the valve seat, sealing it drip-tight and keeping the system piping dry.

Under FIRE or TEST conditions, an electric detection system **(E)**, through a control panel **(C)**, triggers the Solenoid Valve to open. Pressure is released from the control chamber by the opened Solenoid Valve **(4)**, or the Manual Emergency Release **(5)**. The Manual Reset **(3)** prevents line-pressure from entering the control chamber, allowing the main valve to latch open and water to flow into the system piping and to the alarm device.




Valve Closed (Set position)



Valve Opened (operating condition)


DIMENSIONS

VALVE NOMINAL SIZE	A (mm)	B (mm)
50 DN (2”)	320	232
80 DN (3”)	372	232
100 DN (4”)	412	245
150 DN (6”)	462	282
200 DN (8”)	552	332



C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

MATERIALS



NA - PART REPLACEMENT NOT AVAILABLE

* Stainless Steel is standard supply Bronze is optional supply.


** Ductile Iron is standard supply Bronze/Stainless Steel is optional supply.

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

N	DESCRIPTION	QUANTITY			D: DUCTILE IRON ASTM A 536-77 GRADE 65-45-12					S: CAST STEEL ASTM A216-WBC					N: NICKEL ALUMINIUM BRONZE BS1400 Gr AB2				
		8"	6/4"	3/2"	MATERIAL	PART NUMBER				MATERIAL	PART NUMBER				MATERIAL	PART NUMBER			
						8"	6"	4"	3/2"		8"	6"	4"	3/2"		8"	6"	4"	3/2"
1	Housing	1	1	1	Ductile iron	NA	NA	NA	NA	Cast Steel	NA	NA	NA	NA	Al. bronze	NA	NA	NA	NA
2	"O" ring	1	1	1	Neoprene rubber	8561	9783	9784	9791	Neoprene rubber	8561	9783	9784	9791	Neoprene rubber	8561	9783	9784	9791
3	Seat	1	1	1	Stainless Steel*	4025	3993	4003	4017	Stainless Steel*	4025	3993	4003	4017	Al. bronze*	4155	3925	3955	3986
4	Bolt	8	4	-	Stainless Steel	9151	9112	9112	-	Stainless Steel*	9151	9112	9112	-	Monel 400	9898	9899	9899	-
5	Rubber clamp	1	1	1	Ductile iron**	4026	3994	4004	4018	Ductile iron**	4026	3994	4004	4018	Al. bronze**	4156	3926	3956	3984
6	Rubber seat	1	1	1	Neoprene rubber	4027	4000	4005	4023	Neoprene rubber	4027	4000	4005	4023	Neoprene rubber	4027	4000	4005	4023
7	Clapper	1	1	1	Ductile iron**	4034	3990	4011	4041	Ductile iron**	4034	3990	4011	4041	Al. bronze	4153	3927	3953	3985
8	Diaphragm	1	1	1	Neoprene rubber	4035	2427	2507	2786	Neoprene rubber	4035	2427	2507	2786	Neoprene rubber	4035	2427	2507	2786
9	Clamp ring	1	1	1	Ductile iron**	4030	2424	2504	2788	Ductile iron**	4030	2424	2504	2788	Al. bronze	4158	3918	3958	3978
10	Bolt	12	8	8	Stainless Steel	8806	9151	9187	9187	Stainless Steel	8806	9151	9187	9187	Monel 400	9842	9898	9898	9898
11	"O" ring	1	1	1	Neoprene rubber	9986	9986	9986	9986	Neoprene rubber	9986	9986	9986	9986	Neoprene rubber	9986	9986	9986	9986
12	Spindle	1	1	1	Stainless Steel	4029	3996	4007	4020	Stainless Steel	4029	3996	4007	4020	Monel 400	4157	3917	3957	3977
13	nut	1	1	1	Stainless Steel	9185	8838	8838	9185	Stainless Steel	9185	8838	8838	9185	Monel 400	9896	9896	9896	9896
14	Lock nut	1	1	1	Stainless Steel	9186	9184	9184	9186	Stainless Steel	9186	9184	9184	9186	Monel 400	9897	9897	9897	9897
15	Spring	1	1	1	Stainless Steel	2980	2979	2978	2977	Stainless Steel	2980	2979	2978	2977	Inconel-X-750	4154	3914	3954	3974
16	Adaptor	1	1	1	Brass	4033	3998	4010	3983	Brass	4033	3998	4010	3983	Al. bronze	4159	3919	3959	3979
17	Cover	1	1	1	Ductile iron	NA	NA	NA	NA	Cast Steel	NA	NA	NA	NA	Al. bronze	NA	NA	NA	NA
18	Bolt	16	12	12	Carbon Steel	9008	9049	9051	8692	Carbon Steel	9008	9049	9051	8692	Stainless Steel	9841	9841	8804	9123
19	"O" ring	1	1	1	Neoprene rubber	9982	9982	9982	9982	Neoprene rubber	9982	9982	9982	9982	Neoprene rubber	9982	9982	9982	9982
20	Plug	1	1	1	Steel Plated	2514	2514	2514	2514	Steel Plated	2514	2514	2514	2514	Al. bronze	3920	3920	3920	3920
21	Allen bolt	6	-	-	Stainless Steel	8843	-	-	-	Stainless Steel	8843	-	-	-	Stainless Steel	9843	-	-	-

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

FRICTION LOSS



* 2.3 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 594 lpm thru DN 50 AG 400-L
* 4.7 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 1308 lpm thru DN 80 AG 400-L
* 4.7 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 2255 lpm thru DN 100 AG 400-L
* 7.5 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 5117 lpm thru DN 150 AG 400-L
* 8.4 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 8854 lpm thru DN 200 AG 400-L

ORDERING INFORMATION

ASSEMBLED VALVES					
SIZE	VALVE TYPE				
	DUCTILE IRON		STEEL		NICKEL – ALUMINUM – BRONZE
	TRIM TYPE		TRIM TYPE		TRIM TYPE
	GALVANIZED STEEL (175psi)	STAINLESS STEEL AISI316 (250psi)	GALVANIZED STEEL (175psi)	STAINLESS STEEL AISI316 (250psi)	MONEL (250psi)
2” DN50	PDAG400L050E0	PDAG400L050E1	PDAG400L050E2	PDAG400L050E3	PDAG400L050E4
3” DN80	PDAG400L080E0	PDAG400L080E1	PDAG400L080E2	PDAG400L080E3	PDAG400L080E4
4” DN100	PDAG400L100E0	PDAG400L100E1	PDAG400L100E2	PDAG400L100E3	PDAG400L100E4
6” DN150	PDAG400L150E0	PDAG400L150E1	PDAG400L150E2	PDAG400L150E3	PDAG400L150E4
8” DN200	PDAG400L200E0	PDAG400L200E1	PDAG400L200E2	PDAG400L200E3	PDAG400L200E4

SEPARATED COMPONENTS			
SIZE	VALVE		
	DUCTILE IRON	STEEL	NICKEL – ALUMINUM – BRONZE
2” DN50	AG400D050U	AG400S050U	AG400N050U
3” DN80	AG400D080U	AG400S080U	AG400N080U
4” DN100	AG400D100U	AG400S100U	AG400N100U
6” DN150	AG400D150U	AG400S150U	AG400N150U
8” DN200	AG400D200U	AG400S200U	AG400N200U

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

SEPARATED COMPONENTS						
SIZE	TRIM TYPE					
	GALVANIZED STEEL (175psi)		STAINLESS STEEL AISI316 (250psi)		MONEL (250psi)	
	SPARED	PREMOUNTED	SPARED	PREMOUNTED	SPARED	PREMOUNTED
2” DN50	TRDL050080E0	TRDL050080E0P	TRDL050080E3	TRDL050080E3P	TRDL050080E4	TRDL050080E4P
3” DN80	TRDL050080E0	TRDL050080E0P	TRDL050080E3	TRDL050080E3P	TRDL050080E4	TRDL050080E4P
4” DN100	TRDL100200E0	TRDL100200E0P	TRDL100200E3	TRDL100200E3P	TRDL100200E4	TRDL100200E4P
6” DN150	TRDL100200E0	TRDL100200E0P	TRDL100200E3	TRDL100200E3P	TRDL100200E4	TRDL100200E4P
8” DN200	TRDL100200E0	TRDL100200E0P	TRDL100200E3	TRDL100200E3P	TRDL100200E4	TRDL100200E4P

Specify:

Model number	
Type (Actuation)	
Quantity	
Material	
Size of valve	
Flange specification	
Trim materials	
Thread Size	

The equipment presented in this data sheet is to be installed in accordance with the latest published Standards of the national fire protection association (NFPA), FM Global, LPCB, VdS or other similar organizations, also with the provisions of governmental codes or ordinances whenever applicable.
This documentation is not contractual. AG Fire Sprinkler reserves the right to any kind of change without notice.

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08