
DIAPHRAGM DELUGE VALVE LOCAL RESET

MODEL AG 400-L EXTERNAL AND LOCAL RESET
Pneumatic Actuation
(Ductile Iron, Cast Steel, Nickel Aluminum Bronze)

c UL us LISTED 15133

Valve Closed





PRODUCT DESCRIPTION


Deluge Valve is known as a system control valve in a deluge system, used for fast application of water in a spray system. Deluge valve protects areas such as power transformer installation, storage tank, conveyor protection and other industrial application etc. With the addition of foaming agent deluge valve can be used to protect aircraft hangar and inflammable liquid fire.

TECHNICAL DATA

MODEL	AG 400-L
MATERIAL	D: Ductile Iron ASTM A536 S: Cast Steel ASTM A216 WCB N: Nickel Aluminium Bronze BS1400 Gr AB2
NOMINAL SIZE	DN50 (2”), DN80 (3”), DN100 (4”), DN150 (6”) & DN200 (8”)
SEVICE PRESSURE	1.4 to 17.5 Bar (20 to 250 PSI)
THREADED OPENING	BSPT
MOUNTING	Vertical or Horizontal mounting
FACTORY HYDROSTATIC TEST PRESSURE	35 Kg/sq.cm. (500 PSI)
FLANGE CONNECTION	ANSI B 16.5
SERVICE	Without removal from line
TRIM	Galvanized tubing and fittings and nickel lated accessories. Solenoid valve 175 psi Stainless Steel (SS-316) tubing and fittings. Solenoid valve 250 psi Monel tubing and fittings. Ni AL Br Accessories
WET PILOT SPRINKLER HEIGHT LIMITATION	As per graph in the catalogue
NET WEIGHT WITHOUT TRIM	DN50 - 32 Kg DN80 - 35 Kg DN100 - 50 Kg DN150 - 79 Kg DN200 - 153 Kg
FINISH	Red RAL 3000


C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

DELUGE VALVE MODEL: AG 400-L SIZE 50 / 80 / 100 / 150 / 200 DN



C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

DELUGE VALVE MODEL: AG 400-L SIZE 50 / 80 / 100 / 150 / 200 DN



DIMENSION in millimeter (Approximate)

VALVE NOMINAL SIZE	A	B
50 DN	320	232
80 DN	372	232
100 DN	412	245
150 DN	462	282
200 DN	552	332

AG 400-L (DUCTILE IRON ASTM A 536-77 GRADE 65-45-12)

ITEM Nº	PART Nº					DESCRIPTION	QTY				MATERIAL SPECIFICATION
	200 DN	150 DN	100 DN	80 DN	50 DN		200 DN	150 DN	100 DN	80/50 DN	
1	NA	NA	NA	NA	NA	HOUSING	1	1	1	1	DUCTILE IRON
2	8561	9783	9784	9791	9791	“O” RING	1	1	1	1	NEOPRENE RUBBER
3	4025	3993	4003	4017	4017	SEAT	1	1	1	1	STAINLESS STEEL*
4	9151	9112	9112	-	-	BOLT	4	4	-	8	STAINLESS STEEL
5	4026	3994	4004	4018	4018	RUBBER CLAMP	1	1	1	1	DUCTILE IRON **
6	4027	4000	4005	4023	4023	RUBBER SEAT	1	1	1	1	NEOPRENE RUBBER
7	4034	3990	4011	4041	4041	CLAPPER	1	1	1	1	DUCTILE IRON **
8	4035	2427	2507	2786	2786	DIAPHRAGM	1	1	1	1	NEOPRENE RUBBER
9	4030	2424	2504	2788	2788	CLAMP RING	1	1	1	1	DUCTILE IRON **
10	8806	9151	9151	9187	9187	BOLT	8	8	8	12	STAINLESS STEEL
11	9986	9986	9986	9986	9986	“O” RING	1	1	1	1	NEOPRENE RUBBER
12	4029	3996	4007	4020	4020	SPINDLE	1	1	1	1	STAINLESS STEEL
13	9185	8838	8838	9185	9185	NUT	1	1	1	1	STAINLESS STEEL
14	9186	9184	9184	9186	9186	LOCK NUT	1	1	1	1	STAINLESS STEEL
15	2980	2979	2978	2977	2977	SPRING	1	1	1	1	STAINLESS STEEL
16	4033	3998	4010	3983	3983	ADAPTOR	1	1	1	1	BRASS
17	NA	NA	NA	NA	NA	COVER	1	1	1	1	Ductile iron ,
18	9008	9049	9051	8692	8692	BOLT	12	12	12	16	CARBON STEEL
19	9982	9982	9982	9982	9982	“O” RING	1	1	1	1	NEOPRENE RUBBER
20	2514	2514	2514	2514	2514	PLUG	1	1	1	1	STEEL PLATED
21	8843	-	-	-	-	ALLEN BOLT	-	-	-	6	STAINLESS STEEL

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

AG 400-L (NICKEL ALUMINIUM BRONZE BS1400 Gr AB2)											
ITEM Nº	**PART Nº**					**DESCRIPTION**	**QTY**				**MATERIAL SPECIFICATION**
	200 DN	**150 DN**	**100 DN**	**80 DN**	**50 DN**		**200 DN**	**150 DN**	**100 DN**	**80/50 DN**	
1	NA	NA	NA	NA	NA	HOUSING	1	1	1	1	AL. BRONZE BS 1400 - AB2
2	8561	9783	9784	9791	9791	“O” RING	1	1	1	1	NEOPRENE RUBBER
3	4155	3925	3955	3986	3986	SEAT	1	1	1	1	AL. BRONZE BS 1400 - AB2*
4	9898	9899	9899	-	-	BOLT	8	4	4	-	MONEL 400
5	4156	3926	3956	3984	3984	RUBBER CLAMP	1	1	1	1	AL. BRONZE BS 1400 - AB2**
6	4027	4000	4005	4023	4023	RUBBER SEAT	1	1	1	1	NEOPRENE RUBBER
7	4153	3927	3953	3985	3985	CLAPPER	1	1	1	1	AL. BRONZE BS 1400 - AB2
8	4035	2427	2507	2786	2786	DIAPHRAGM	1	1	1	1	NEOPRENE RUBBER
9	4158	3918	3958	3978	3978	CLAMP RING	1	1	1	1	AL. BRONZE BS 1400 - AB2
10	9842	9898	9898	9898	9898	BOLT	12	8	8	8	MONEL 400
11	9986	9986	9986	9986	9986	“O” RING	1	1	1	1	NEOPRENE RUBBER
12	4157	3917	3957	3977	3977	SPINDLE	1	1	1	1	MONEL 400
13	9896	9896	9896	9896	9896	NUT	1	1	1	1	MONEL 400
14	9897	9897	9897	9897	9897	LOCK NUT	1	1	1	1	MONEL 400
15	4154	3914	3954	3974	3974	SPRING	1	1	1	1	INCONEL-X-750
16	4159	3919	3959	3979	3979	ADAPTOR	1	1	1	1	AL. BRONZE BS 1400 - AB2
17	NA	NA	NA	NA	NA	COVER	1	1	1	1	AL. BRONZE BS 1400 - AB2
18	9841	9841	8801	9123	9123	BOLT	16	12	12	12	STAINLESS STEEL
19	9982	9982	9982	9982	9982	“O” RING	1	1	1	1	NEOPRENE RUBBER
20	3920	3920	3920	3920	3920	PLUG	1	1	1	1	AL. BRONZE BS 1400 - AB2
21	9843	-	-	-	-	ALLEN BOLT	6	-	-	-	MONEL 400


C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

AG 400-L (CAST STEEL ASTM A216-WBC)											
ITEM Nº	PART Nº					DESCRIPTION	QTY				MATERIAL SPECIFICATION
	200 DN	150 DN	100 DN	80 DN	50 DN		200 DN	150 DN	100 DN	80/50 DN	
1	NA	NA	NA	NA	NA	HOUSING	1	1	1	1	CAST STEEL
2	8561	9783	9784	9791	9791	“O” RING	1	1	1	1	NEOPRENE RUBBER
3	4025	3993	4003	4017	4017	SEAT	1	1	1	1	STAINLESS STEEL*
4	9151	9112	9112	-	-	BOLT	4	4	-	8	STAINLESS STEEL
5	4026	3994	4004	4018	4018	RUBBER CLAMP	1	1	1	1	DUCTILE IRON **
6	4027	4000	4005	4023	4023	RUBBER SEAT	1	1	1	1	NEOPRENE RUBBER
7	4034	3990	4011	4041	4041	CLAPPER	1	1	1	1	DUCTILE IRON **
8	4035	2427	2507	2786	2786	DIAPHRAGM	1	1	1	1	NEOPRENE RUBBER
9	4030	2424	2504	2788	2788	CLAMP RING	1	1	1	1	DUCTILE IRON **
10	8806	9151	9151	9187	9187	BOLT	8	8	8	12	STAINLESS STEEL
11	9986	9986	9986	9986	9986	“O” RING	1	1	1	1	NEOPRENE RUBBER
12	4029	3996	4007	4020	4020	SPINDLE	1	1	1	1	STAINLESS STEEL
13	9185	8838	8838	9185	9185	NUT	1	1	1	1	STAINLESS STEEL
14	9186	9184	9184	9186	9186	LOCK NUT	1	1	1	1	STAINLESS STEEL
15	2980	2979	2978	2977	2977	SPRING	1	1	1	1	STAINLESS STEEL
16	4033	3998	4010	3983	3983	ADAPTOR	1	1	1	1	BRASS
17	NA	NA	NA	NA	NA	COVER	1	1	1	1	CAST STEEL
18	9008	9049	9051	8692	8692	BOLT	12	12	12	16	CARBON STEEL
19	9982	9982	9982	9982	9982	“O” RING	1	1	1	1	NEOPRENE RUBBER
20	2514	2514	2514	2514	2514	PLUG	1	1	1	1	STEEL PLATED
21	8843	-	-	-	-	ALLEN BOLT	-	-	-	6	STAINLESS STEEL

NA - PART REPLACEMENT NOT AVAILABLE
* Stainless Steel is standard supply Bronze is optional supply.
** Ductile Iron is standard supply Bronze/Stainless Steel is optional supply.

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

FRICTION LOSS MODEL AG 400-L



* 2.3 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 594 lpm thru DN 50 AG 400-L
* 4.7 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 1308 lpm thru DN 80 AG 400-L
* 4.7 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 2255 lpm thru DN 100 AG 400-L
* 7.5 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 5117 lpm thru DN 150 AG 400-L
* 8.4 PSI Pressure loss @ 15 feet per second (4,57 m/s) velocity having flow of 8854 lpm thru DN 200 AG 400-L

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08


OPERATION

The Model AG 400-L from AG Fire Sprinkler is suitable for systems that include dry pilot lines with closed pneumatic fusible plugs (thermal releases), and piping systems with a wide variety of open nozzles. Since it is pneumatically controlled, the Model AG 400-L is recommended for environments with freezing temperatures and/or corrosive water supply.


In the SET position, the line-pressure supplied to the main valve's control chamber **(1)** via the priming line **(2)** and through an Manual Reset **(3)**, is trapped by the Manual Reset **(3)** internal check valve, by a closed Pneumatic Pressure Operated Relief Valve **(4)** and by a closed Manual Emergency Release **(5)**. The trapped pressure holds the main valve's diaphragm and plug against the valve seat, sealing it drip-tight and keeping the system piping dry.

The Pneumatic Pressure Operated Relief Valve **(4)** is held closed by the pneumatic pressure maintained in the dry pilot line **(7)**.

Under FIRE or TEST conditions, a pilot line pneumatic pressure drop opens the Pneumatic Pressure Operated Relief Valve **(4)**. Pressure is then released from the main valve's control chamber through the opened Pneumatic Pressure Operated Relief Valve **(4)**, or the Manual Emergency Release. The Manual Reset **(3)** prevents line pressure from entering the control chamber, allowing the main valve to latch open and water to flow into the system piping and to the alarm device.



Valve Closed (Set position)



Valve Opened (operating condition)

ORDERING INFORMATION

ASSEMBLED VALVES					
SIZE	VALVE TYPE				
	DUCTILE IRON		STEEL		NICKEL – ALUMINUM – BRONZE
	TRIM TYPE		TRIM TYPE		TRIM TYPE
	GALVANIZED STEEL	STAINLESS STEEL AISI316	GALVANIZED STEEL	STAINLESS STEEL AISI316	MONEL
2" DN50	PDAG400L050N0	PDAG400L050N1	PDAG400L050N2	PDAG400L050N3	PDAG400L050N4
3" DN80	PDAG400L080N0	PDAG400L080N1	PDAG400L080N2	PDAG400L080N3	PDAG400L080N4
4" DN100	PDAG400L100N0	PDAG400L100N1	PDAG400L100N2	PDAG400L100N3	PDAG400L100N4
6" DN150	PDAG400L150N0	PDAG400L150N1	PDAG400L150N2	PDAG400L150N3	PDAG400L150N4
8" DN200	PDAG400L200N0	PDAG400L200N1	PDAG400L200N2	PDAG400L200N3	PDAG400L200N4

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

SEPARATED COMPONENTS			
SIZE	VALVE		
	DUCTILE IRON	STEEL	NICKEL – ALUMINUM – BRONZE
2” DN50	AG400D050U	AG400S050U	AG400N050U
3” DN80	AG400D080U	AG400S080U	AG400N080U
4” DN100	AG400D100U	AG400S100U	AG400N100U
6” DN150	AG400D150U	AG400S150U	AG400N150U
8” DN200	AG400D200U	AG400S200U	AG400N200U

SEPARATED COMPONENTS						
SIZE	TRIM TYPE					
	GALVANIZED STEEL		STAINLESS STEEL AISI316		MONEL	
	SPARED	PREMOUNTED	SPARED	PREMOUNTED	SPARED	PREMOUNTED
2” DN50	TRDL050080N0	TRDL050080N0P	TRDL050080N3	TRDL050080N3P	TRDL050080N4	TRDL050080N4P
3” DN80	TRDL050080N0	TRDL050080N0P	TRDL050080N3	TRDL050080N3P	TRDL050080N4	TRDL050080N4P
4” DN100	TRDL100200N0	TRDL100200N0P	TRDL100200N3	TRDL100200N3P	TRDL100200N4	TRDL100200N4P
6” DN150	TRDL100200N0	TRDL100200N0P	TRDL100200N3	TRDL100200N3P	TRDL100200N4	TRDL100200N4P
8” DN200	TRDL100200N0	TRDL100200N0P	TRDL100200N3	TRDL100200N3P	TRDL100200N4	TRDL100200N4P

Specify:

Model number	
Type (Actuation)	
Quantity	
Material	
Size of valve	
Flange specification	
Trim materials	
Thread Size	

The equipment presented in this data sheet is to be installed in accordance with the latest published Standards of the national fire protection association (NFPA), FM Global, LPCB, VdS or other similar organizations, also with the provisions of governmental codes or ordinances whenever applicable.
This documentation is not contractual. AG Fire Sprinkler reserves the right to any kind of change without notice.

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08