HYDRANTS

Models: AG-RM 4xC & AG-RM 6xC
Blind steel hydrant



PRODUCT DESCRIPTION


The model AGRM6-4 is a special fire protection hydrant that would ease the access to the water supplied by an underground piping system. This model has several different connections and water flow rates. Each outlet has its own shut-off valve.

TECHNICAL DATA

Models	AG-RM 4xC AG-RM 6xC
Working pressure	200 psi (14 bar)
Hose connection (laterals)	2 x 2 1/2" Male or female (depending on the valve selected)
Flange connection	Inlet: Flange ANSI FF Ø6" # 150 (AG-RM 6xC) Flange ANSI FF Ø4" #150 (AG-RM 4xC) Outlet: Blind
Material	Cast Steel
Finish	Red RAL 3000

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08

DIMENSIONS



INSTALLATION

Before installing the AGRC6-4 check that all the components have no failure or slightly damage. Confirm that all the shut-off valves are completely closed.

This wet barrel hydrants should be located in places where the freezing is unusual because it could freeze the water and broke the hydrants at the flanges.

ORDERING INFORMATION

BODY SIZE	CODE
4” DN100	36000743
6” DN150	36000745

Specify:

Model	
Quantity	
Outlet connection	
Hose valves	Ordered separately

The equipment presented in this bulletin is to be installed in accordance with the latest published Standard of the National Fire Protection Association, Factory Mutual Research Corporation, or other similar organizations and also with the provisions of governmental codes or ordinances whenever applicable.
This documentation is not contractual. AG Fire Sprinkler reserves the right to any kind of change without notice.

C/Alfoz de Bricia nº4 | P.I. Villalonquéjar | 09001 Burgos (Spain) | Tlfno: +34 947 28 11 08